

- ✓ Live rotation under maximum pressure
- ✓ Complete stainless steel construction
- ✓ Single bearing system
- ✓ Corrosion resistant
- ✓ Maintenance free









Application

HP-guns, high pressure hose reels, hydraulics, tangle-free applications

TECHNICAL DATA

| | |
|--------------------------|----------------------------------------------------------|
| Pressure | 500 bar (50 MPa) |
| Temperature | 120°C |
| RPM | max. 30 rpm |
| Body | stainless steel |
| Inner part Seal | stainless steel O-ring NBR (optional: EPDM or FKM) |
| Bearing | 1x thrust ball bearing |
| Throughput medium | pH 3 - 12 10 µm filtered 20 bar compressed air |



DGVI

| Part No. | G1 | G2 (F) | NW | SW1 | SW2 | L1 | L2 | Weight |
|----------|---------|---------|----|-----|-----|----|----|--------|
| 32.702 | R1/4" M | G1/4" F | 6 | 24 | 19 | 54 | 10 | 150 g |
| 32.724 | R3/8" M | G3/8" F | 6 | 24 | 22 | 56 | 10 | 160 g |
| 32.734 | G3/8" M | G3/8" F | 6 | 24 | 22 | 64 | 10 | 170 g |
| 32.814 | G1/2" M | G1/2" F | 9 | 27 | 27 | 75 | 15 | 250 g |

| Part No. | G1 (F) | G2 (M) | NW | SW1 | SW2 | L1 | L2 | Weight |
|----------|---------|---------|----|-----|-----|----|----|--------|
| 32.781 | G1/4" F | G1/4" M | 6 | 24 | 19 | 64 | 11 | 160 g |
| 32.783 | G1/4" F | G3/8" M | 6 | 24 | 19 | 65 | 12 | 170 g |

| Part No. | G1 (F) | G2 (F) | NW | SW1 | SW2 | L1 | Weight |
|----------|---------|---------|----|-----|-----|----|--------|
| 32.782 | G1/4" F | G1/4" F | 6 | 24 | 19 | 66 | 190 g |
| 32.784 | G1/4" F | G3/8" F | 6 | 24 | 22 | 68 | 200 g |

| Part No. | G1 (F) | G2 (QV) | NW | SW1 | SW2 | L1 | L2 | Weight |
|----------|---------|-----------|----|-----|-----|----|----|--------|
| 32.787 | G1/4" F | M18x1.5 M | 6 | 24 | 19 | 62 | 10 | 140 g |
| 32.788 | G1/4" F | M21x1.5 M | 6 | 24 | 22 | 66 | 14 | 150 g |
| 32.789 | G1/4" F | M22x1.5 M | 6 | 24 | 22 | 66 | 14 | 160 g |

DGV Heat Shield

| Part No. | Packing unit | Weight |
|----------|--------------|--------|
| 28.973 | 15 pieces | 35 g |

Legend

M., = metric thrust, ..M = male, F = female, G = gas pipe thrust, R = gas pipe thrust conical, QV = quick connects
SV = profile ring fitting, D = diameter, L = length, NW = nominal width, SW = wrench size

Additional Seal Options available

EPDM (E) or FKM/Viton (V). Please indicate letter of seal material after part number. Minimum orders apply.